

# PERFECT FOR THE IVECO DAILY 70C

## FlexBox DRY

- ▶ 30 mm sandwich panels
- ▶ Insulated roof fitted as standard
- ▶ Double-hinged rear doors
- ▶ Rear portal & auxiliary frame hot-dip galvanised
- ▶ LED interior lighting with motion detector
- ▶ Sliding tie-down points on the floor
- ▶ Step with handgrip at the rear
- ▶ Plastic mudguards with dirt collectors
- ▶ Lighting according to German Road Traffic Regulations (StVZO)



The FLEXBOX superstructures are checked by TÜV NORD according to Code XL.



## FlexBox COOL

- ▶ 60 mm sandwich panels
- ▶ 65 mm insulated floor
- ▶ Double-hinged rear doors
- ▶ Auxiliary frame hot-dip galvanised, rear portal made of stainless steel
- ▶ LED interior lighting with motion detector
- ▶ Step with handgrip at the rear
- ▶ Plastic mudguards with dirt collectors
- ▶ Lighting according to German Road Traffic Regulations (StVZO)

Carrier aggregates, Konvekta, Mitsubishi and Thermo King



## FlexBox FREEZE

- ▶ 80 mm front wall & roof
- ▶ 65 mm side wall panels
- ▶ 120 mm insulated floor
- ▶ 85 mm double-hinged rear doors
- ▶ Auxiliary frame hot-dip galvanised, rear portal made of stainless steel
- ▶ LED interior lighting with motion detector
- ▶ Step with handgrip at the rear
- ▶ Plastic mudguards with dirt collectors
- ▶ Lighting according to German Road Traffic Regulations (StVZO)



Carrier aggregates, Konvekta, Mitsubishi and Thermo King



The FLEXBOX superstructures are certified in accordance with ATP and HACCP regulations.

# PERFECT FOR THE IVECO DAILY 70C

Additional accessories and individual design solutions on request!



**SUPER LIGHTWEIGHT** HUMBAUR GFK TECHNOLOGY

FLEXBOX DRY	W/B 3450 mm	3750 mm	4100 mm	4350 mm	4750 mm	5100 mm
Internal Dim. (L x W x H) in mm	3685 x 2035 x 2085	4185 x 2035 x 2085	4435 x 2035 x 2085	4935 x 2035 x 2085	5685 x 2035 x 2085	5685 x 2035 x 2085
Steel construction weight in kg	700	770	805	875	980	980
GRP structure weight in kg	390	430	450	490	550	550

  

FLEXBOX COOL	W/B 3450 mm	3750 mm	4100 mm	4350 mm	4750 mm	5100 mm
Internal Dim. (L x W x H) in mm	3620 x 2070 x 2065	4120 x 2070 x 2065	4370 x 2070 x 2065	4870 x 2070 x 2065	5620 x 2070 x 2065	5620 x 2070 x 2065
Steel construction weight in kg	895	985	1030	1120	1255	1255
GRP structure weight in kg	595	655	685	745	835	835

  

FLEXBOX FREEZE	W/B 3450 mm	3750 mm	4100 mm	4350 mm	4750 mm	5100 mm
Internal Dim. (L x W x H) in mm	3570 x 2050 x 1970	4070 x 2050 x 1970	4320 x 2050 x 1970	4820 x 2050 x 1970	5570 x 2050 x 1970	5570 x 2050 x 1970
Steel construction weight in kg	1000	1100	1150	1250	1400	1400
GRP structure weight in kg	670	740	775	845	950	950